

# scoot<sup>TM</sup>

## HOW TO GUIDE SCOOTER HOOK

Three easy steps to attach your Scooter Hook (Patent Pending)

1. First, decide where you want to carry the scooter.

For smaller scooters, such as a Mini Micro Scooter® or an Iscoot, you can carry the scooter along the side of the buggy, with the front of the scooter facing backwards. In this instance wrap the velcro strap around the side of the buggy handlebar, with the hook facing towards the person pushing the buggy (see picture 1).

For larger scooters, such as a Maxi Micro Scooter®, a Razor® or JD Bug®, you can carry the scooter along the back of the buggy. Attach the velcro strap to the top of the buggy handlebars with the hook facing inwards (see picture 2). This is a great place for the hook if you want to carry loads of shopping bags too!

Either of these positions work for doublebuggies, such as Phil & Teds®.

2. Next wrap the velcro strap around your buggies handlebar as tight as you can. Make sure the strap goes all the way round and the velcro meets as much as possible. This will make it really strong.

3. Try out the scooter on the hook. Check that the scooter isn't touching the buggy wheels. If they do either fasten the scoot hook further up the handlebar or reposition your buggy handlebar to give you more height.

I hope the Scooter Hook makes your life a lot easier and safer.



Picture 1



Picture 2